



VERSATILE, COMPLETELY PORTABLE, LIGHTWEIGHT, HANDHELD WITH NO TRAILING LEADS
RANGE OF AVAILABLE ACCESSORIES
CAN BE CHARGED VIA THE MAINS AND CAR
FREE CAR CHARGER INCLUDED



PRO & MAGPACK
TK10YCW

Light source	10W
Dimensions	6 x 10 x 6 inches
Luminous flux	700+ Lm
Color temperature	5,500 - 6,000K
Colour rendering index	RA > 70
Housing material	Aluminium & Iron
Adaptor (input)	100-240V AC 50/60Hz
Operating temperature	-25°C to 50°C // -13°F to 122°F
Beam angle	120°
Battery specifications	7.4V 4.4Ah Li-Ion
Charging time	5 Hours*
Working time	4 Hours*
Certificates	CE / IP65 / RoHS / CSA / UL



PRO & MAGPACK
TK10CACW

Light source	10W
Dimensions	6 x 10 x 6 inches
Luminous flux	700+ Lm
Color temperature	5,500 - 6,000K
Colour rendering index	RA > 70
Housing material	Aluminium & Iron
Adaptor (input)	100-240V AC 50/60Hz
Operating temperature	-25°C to 50°C // -13°F to 122°F
Beam angle	120°
Battery specifications	7.4V 4.4Ah Li-Ion
Charging time	5 Hours*
Working time	4 Hours*
Certificates	CE / IP65 / RoHS / CSA / UL



MAGPACK
TK10MP



CLAMP
TK10CLP



TRIPOD
TK1020Y

*Environmental conditions will affect the rate of charging and discharging

AVAILABLE TO YOUR CUSTOM SPECIFICATIONS, DIRECT FROM THE FACTORY

